EXIDE MILEAGE

- Robust design - to take care of stringent application requirements
- Special side vented cover design - excellent spill-resistant characteristics
- Double clad separation - high reliability and life expectancy ensures customer satisfaction
- Technology - to suit high temperature applications
- Appearance - rugged with appealing cosmetics
- Magic Eye - for determination of electrolyte level and state-of-charge
- Easy to use - batteries delivered in factory-charged, ready-to-use condition

60 Month Warranty *
(30 FOC + 30 PRO-RATA)
* T&C Apply

Technical Specifications of Exide Mileage Range of Batteries

Battery Nomenclature	Ref C20 Capacity (Ah)	Maximum Overall Dimensions (MM)			Nominal Filled Weight	Electrolyte Volume	Charging Current (A)	CCA at - 18°C As Per			Acid Level Indicator	Battery Layout
		L	W	H	(KG)	(LITRES)		EN	IEC	SAE		
FML8-ML35R	35	197	129	227	10.6	2.2	3	-	270	332	PRESENT	Right Layout -▭▭▭▭+
FML8-ML35L	35	197	129	227	10.6	2.2	3	-	270	332	PRESENT	Left Layout +▭▭▭▭-
FML0-ML38B20L	35	197	129	227	10.5	2.2	3	-	270	332	PRESENT	Left Layout +▭▭▭▭-
FML0-ML38B20R	35	197	129	227	10.5	2.2	3	-	270	332	PRESENT	Right Layout -▭▭▭▭+
FML8-ML40LBH	40	197	137	227	11	2	3	-	280	354	PRESENT	Left Layout +▭▭▭▭-
FML0-ML40RBH	40	197	137	227	11	2	3	-	280	354	PRESENT	Right Layout -▭▭▭▭+
FML0-MLDIN50	50	207	175	190	14	2.8	4	405	-	-	PRESENT	Left Layout +▭▭▭▭-
FML8-MLDIN65LH	65	278	175	175	18.4	3.5	5	500	-	-	PRESENT	Left Layout +▭▭▭▭-
FML0-ML45D21LBH	45	205	177	222	14.3	3.2	3.5	-	330	410	PRESENT	Left Layout +▭▭▭▭-
FML0-ML55D23L	54	231	173	223	16	3.6	4.5	-	360	450	PRESENT	Left Layout +▭▭▭▭-
FML0-ML75D23LBH	68	231	175	223	17.3	3.5	5	-	450	565	PRESENT	Left Layout +▭▭▭▭-
FML0-MLDIN44LH	44	210	175	175	13	2.6	3.5	360	-	-	PRESENT	Left Layout +▭▭▭▭-
FML0-MLDIN55	55	242	175	190	16.8	3.35	4.5	480	-	-	PRESENT	Left Layout +▭▭▭▭-
FML0-MLDIN55R	55	242	175	190	16.8	3.35	4.5	480	-	-	PRESENT	Right Layout -▭▭▭▭+
FML0-MLDIN60	60	242	175	190	16.8	3.35	5	500	-	-	PRESENT	Left Layout +▭▭▭▭-
FML0-MLDIN44R	44	207	175	190	13	2.9	3.5	360	-	-	PRESENT	Right Layout -▭▭▭▭+
FML0-MLDIN80	80	315	175	190	22.8	6.2	6.5	760	-	-	PRESENT	Left Layout +▭▭▭▭-
FML0-MLDIN66	66	278	175	190	20.1	3.8	5	590	-	-	PRESENT	Left Layout +▭▭▭▭-